

**SINGLE WHEEL BARROW** Capacity 200 Kg., 80 lit. @ 3 cft.



Load capacity - 200 kg.  
 Volumetric capacity - 80 liters @ 3 CFT  
 Overall size - L 1300 x W 550 x H 750 mm  
 Size of pan at bottom - 400 x 600 mm  
 Size of pan at top - 400 x 800 mm  
 Trolley Weight - 35 to 40 Kg.  
 Wheel - Dia 300 x Width 50 mm - 1 No.

**DOUBLE WHEEL BARROW** Capacity 200 Kg., 80 lit @ 3 cft.



Load capacity - 200 kg.  
 Volumetric capacity - 80 liters @ 3 CFT  
 Overall size - L 1300 x W 550 x H 750 mm  
 Size of pan at bottom - 400 x 600 mm  
 Size of pan at top - 400 x 800 mm  
 Trolley Weight - 35 to 40 kg.  
 Wheel - Dia 300 x Width 50 mm - 2 Nos.

**PLATFORM TROLLEY** Sizes - 900 x 600, 1250 x 750, 1500 x 900 mm



These trolleys are extensively used for movement of corrugated boxes, gunny bags, heavy material, crates etc. within factories, godowns, stores & wear houses. The platform consists of 2.5 mm ms sheet on fabricated angle frame made of ms angle 40 x 40 x 2.5 mm.

	900 x 600	1250 x 750	1500 x 900
Load Carrying Capacity	750 Kg.	1000 Kg.	1250 Kg.
2 Fixed & Swivel Castors	150 x 50 mm	200 x 50 mm	200 x 50 mm

All wheels with ball bearings.

**WORKSHOP TROLLEY** Sizes - 900 x 600, 1250 x 750 mm



These trolleys are extensively used for movement of loose components within factories, godowns, stores and wear houses. Trolley is provided with a wire mesh netting on all four sides of platform. The platform consists of 2.5 mm ms sheet on fabricated angle frame made of ms angle 40 x 40 x 2.5 mm

	900 x 600	1250 x 750
Load Carrying Capacity	750 Kg.	1000 Kg.
2 Fixed & Swivel Castors	150 x 50 mm	200 x 50 mm

All wheels with ball bearings.

**SHELF TROLLEY** Sizes : 900 x 600, 1250 x 750 mm



Used for movement of corrugated boxes, heavy material, crates etc., within factories, godowns, stores and wear houses. These trolleys can be used as workstation near machines for placing jobs.

	900 x 600	1250 x 750
Load Carrying Capacity	750 Kg.	1000 Kg.
2 Fixed & Swivel Castors	150 x 50 mm	200 x 50 mm

All wheels with ball bearings.

**UNIVERSAL TROLLEY** Capacity : 1000 Kg. Sizes : 600 x 900, 1250 x 750 mm.



This trolley is similar to pallet truck in construction but without any hydraulic pump and without up and down movement of platform. The spring loaded handle with thrust bearing and ball at top gives excellent maneuverability under heavy loads.

- Load Carrying Capacity - 1000 Kg.
- Wheels - 200 x 50 - 2 Nos & - 150 x 50 - 2 Nos.
- Platform height from ground - 170 mm.

All wheels with ball bearings.

**SACK TROLLEY** Capacity : 150 Kg.



This trolley is designed for easy movement of gunny bags in sugar factories, rice and dal mills, in godowns etc. The trolley is fabricated from 1" A class m.s. pipe pressed into elliptical shape for sturdy construction, and m.s. flat 40 x 6 mm.

- Load Carrying Capacity - 150 Kg.
- Total trolley weight - @ 18 Kg.
- Overall Dimension - L 1150 x W 420
- Width at nose 350, at handle 420 mm.
- Wheels - Dia 200 x Width 50 mm - 2 Nos.

**MULTI UTILITY TROLLEY** Capacity : 300 Kg.



This trolley is designed for easy movement of corrugated boxes. The trolley is fabricated from angle 40 x 40 x 2.5 with 1" pipe handle. The front nose is @ 300 mm long with ribbed at bottom for additional strength.

Additional hinged platform is provided for extra width boxes as a bottom support.

- Load Carrying Capacity - 300 Kg.
- Overall Size - L 1100 x W 600 mm.
- Nose length - 300 mm.
- Hinged Platform Length - 450 mm
- Self weight - @ 25 Kg.
- Wheels - Dia 200 x 50 mm - 2 Nos.

## GAS CYLINDER TROLLEY (SINGLE CYLINDER)

For CO<sub>2</sub> & O<sub>2</sub>, with two and three wheels and locking safety chain



TWO WHEEL TROLLEY    THREE WHEEL TROLLEY    TROLLEY WITH CYLINDER

These trolleys are extensively used for movement of oxygen cylinders, carbon dioxide cylinders, LPG cylinders within factories, godowns, stores and wear houses.

- Load Carrying Capacity - 100 Kg.
- Trolley self weight - @ 25 Kg.
- Wheels - Dia 200 x 50 mm - 2 Nos.
- Swivel Castor 125 x 32 mm - 1 Nos.

## GAS CYLINDER TROLLEY (DOUBLE CYLINDER)

(For LPG & CO<sub>2</sub> or O<sub>2</sub>, with three wheels and locking safety chain)



These trolleys are extensively used for movement of oxygen cylinders, carbon dioxide cylinders, LPG cylinders within factories, godowns, stores and wear houses.

- Load carrying capacity - 200 Kg.
- Trolley self weight - @ 35 Kg.
- Wheels - Dia 200 x 50 mm - 2 Nos.
- Swivel castor 125 x 32 mm - 1 Nos.

## DRUM TROLLEY Capacity : 300 Kg.



This trolley is designed for easy movement of 210 lit of drums from one place to other in chemical factories, oil depots, factories etc. The trolley is fabricated from m.s. angle 40x40x6 mm m.s. flats and 1" A class m.s. pipe.

- Load carrying capacity - 300 Kg.
- Total trolley weight - @ 45 Kg.
- Wheels fitted - Dia 200 x 50 mm - 2 Nos.
- Swivel castor 125 x 50 mm - 1 Nos.
- Overall Size - L 1550 x W 650 x H 850 mm

## STEEL PALLETS Capacity : 3000 to 5000 kg.



Steel Pallets are fabricated from 2.5 mm m.s. sheet at top with angle 40 x 40 x 2.5 mm ribbed at bottom. Special purpose heavy duty legs at four corners are provided with 120 mm ground clearance for easy entry of pallet truck.

- Steel Pallet - 1000 x 1000 mm.
- Load carrying capacity - 3000 Kg.
- Self weight - @ 32 Kg.
- Steel Pallet - 1250 x 1250 mm.
- Load carrying capacity - 3000 Kg.
- Self weight - @ 40 Kg.

### CHIP TROLLEY Capacity : 200 Kg.



- Load Carrying Cap. - 200 Kg., @ 4 cft.
- Top Size - 710 x 580 mm
- Bottom Size 320 x 580, Depth 550 mm.
- Trolley will be with Hard Polymer wheels 150 x 50 with sealed Ball bearings.
- Overall size of base frame - L 760 x W 600 mm.
- Provided with foot operated spring loaded lever for trolley tilting so that material can be removed easily.

### COOLANT FEEDING TROLLEY Capacity : 200 Lit Size : 1250 x 750 mm.



- Load carrying capacity - 300 Kg.
- Coolant tank capacity - @ 200 lit
- Fitted with 0.25 HP 'Crompton' single phase Water pump with 5 mtr 1" PVC pipe with hook.
- Trolley is with 'Crompton' plug with 5 mtr wire and a motor on / off switch with MCB for safety.
- Wheels - Dia 200 x 50 mm - 2 Nos. & Dia 150 x 50 mm - 2 Nos.
- Construction of trolley is similar to Universal trolley.

### TOOL TROLLEY Size 600 x 900 mm



- Provided with plastic tool pockets in three sizes BT - 30, BT - 40, & BT - 50
- Provided with 2 fixed & 2 swivel castor for easy movement on shop floor.
- Systematic & vertical storage of tools.
- Protection from scratches, dents etc, to tools due to unique design & high quality engineering plastic material.
- Instant identification of tools.

### WORK TABLES , ASSEMBLY TABLES Size : 600 x 1000, 600 x 1500



- With two lockable doors with middle partition.
- Provided with vertical structure frame for drawing attachment with removable hooks.

#### OPTIONAL EXTRAS

- Arrangement is made for writing the on line inspection report.
- Rubber sheet 4 mm over shelves & top portion.
- Table with castor wheels for easy movement of table.

## CRATE & BIN TROLLEYS

Sizes : 600 X 900, 600 X 1250 MM



SINGLE SIDE CRATE TROLLEY

DOUBLE SIDE CRATE TROLLEY

CUSTOM BUILT MODULAR CRATE TROLLEY

- These trolleys are used for movement of material stored in plastic bins in a systematic way.
- Mainly used on shop floors as mini stores, on assembly lines, for storing of various components.
- We also manufacture custom built trolleys as per customer's requirements.

## INDUCTION FURNACE CHARGING RAIL TROLLEY

Capacity : 1000 kg.



- Fully Automatic, operated by push buttons .
- To and fro movement on straight rail from scrap yard to furnace by gear box coupled with electric motor.
- Tilting by electro hydraulic power pack connected to hydraulic cylinders.
- To, Fro, Up & Down all movements controlled by limit switches.

- *Kotibhaskar Material Handling Equipments reserves the rights to introduce changes without prior notice.*
- *Copyright in the above material subsists in common law with the company. No portion of the material or the entire material may be photo copied in any manner without the prior approval of the company.*

The Manufacturer and Exporter :

### **KOTIBHASKAR MATERIAL HANDLING EQUIPMENTS**

Plot No. K-3/2/1, Additional M.I.D.C., Satara - 415 004.

• Ph : (02162) 248139 , 248129 , 248138 | Fax : (02162) 248652 | Cell : 98224 13252 , 92267 36597 |  
| Email : premierkmhe@dataone.in , amodsatara@sancharnet.in | Website : www.kotibhaskar.in |

SHIPRA ASSOCIATES 9822040094

